SA SANDBAGS
Geotextile Sandbag Solutions

Specification Sheet

Mini Sandbags

F34 geotextile mini sandbags for lightweight ballast

F34 Nonwoven Geotextile — Material tested in accordance with ASTM and EN ISO standards for geotextile performance



TECHNICAL SPECIFICATIONS

PROPERTY	VALUE	TEST METHOD
Thickness at 2 kPa	**1.0 mm**	ASTM D5199
CBR Puncture Strength	**2,600 N**	ASTM D6241
Tensile Strength (MD/CMD)	**15/15 kN/m**	ASTM D4595
Elongation at Break	**40-65%**	ASTM D4595
Trapezoidal Tear	**250/250 N**	ASTM D4533
Grab Tensile	**995/900 N**	ASTM D4632
Grab Elongation at Break	**>45%**	ASTM D4632
Water Flow (50mm water head)	**30**	ASTM D4491
Permeability (50mm water head)	**7**	ASTM D4491
Pore Size (O95%)	**<90**	ASTM D4751
UV Stability	**Min 70% retained strength after 500 hrs**	ASTM D7238
Durability	**Tested**	EN ISO 13348
Rot Resistance	**Non-biodegradable - rot and moisture proof**	

SIZES

SIZE	DIMENSIONS (W × H)	FILLED WEIGHT
Mini Sandbag	—	1-3kg

Bags ship empty (unfilled). Dimensions are nominal flat sizes; filled weights vary with the fill material and how full the bag is packed. Specifications may change without notice — current pricing, stock and the latest version of this sheet are at sasandbags.co.za/products/mini-sandbags

SA Sandbag Solutions (Pty) Ltd
+27 79 104 4404 · info@sasandbags.co.za · sasandbags.co.za